




**QMI SPU4-HB, SPU8-HB AND SPU12-HB HAMMER BLOW STYLE
SINGLE-HOLE PUNCH UNITS**

The QMI Hammer Blow Style Single Punch Units allow for the perforation of single lines of holes down a web that is moving continuously or intermittently. The units are designed for use when higher gage film, gusseted webs, etc require a solid contact between plunger and die. Units having different throat depths can be set up in groups on one or both sides of a web to provide multiple lines of holes.

KEY FEATURES INCLUDE:

- Utilizes an air cylinder, plunger and die to provide a momentary solid contact with the web.
- Provides excellent hole quality in heavy and gusseted films.
- Standard mounting bracket allows bolt-on installation on most bag machines and other equipment.
- Can be mounted on a floor stand to allow movement from line to line.
- Punches clean round holes, butterfly, cross cut and half moon holes from 1/8” through 7/16” in 1/16” increments.
- Standard air regulator, valve and manifold in 12V, 24V or 110V.
- When coupled with a QMI PLC Control System and optical encoder, various patterns can be created and very good hole quality can be produced.
- May also be controlled by a cam-mounted micro-switch or with a signal from a bag machine or other equipment.
- Dies can be re-sharpened to provide long lifecycles.



QM-SPU12-HB Shown

In line with our policy of continual research and development, we reserve the right to alter machine specifications without notice. Copyright ©QMI, Inc. All rights reserved

PO BOX 931, Pryor, Oklahoma 74362-0931 Phone (918) 825-5777 FAX (918) 825-7773

www.qmi-inc.net sales@qmi-inc.net